



**B** HYDROPHOBIC 200 MESH SCREEN (74 MICRONS)

1. CORROSION RESISTANT METAL END CAPS/CENTERTUBE
2. BUNA N GASKETS
3. 250°F MAX. TEMPERATURE

B	ADDED NOTES	DAN	7/11/12	LTH
A	ADDED SHOCK TEST REQUIREMENT	ML	3/04	ML
REV	DESCRIPTION	BY	DATE	APP

THE INFORMATION AND DATA CONTAINED HEREIN CONFORMS TO ASME Y14.5-M 1994

DRAWING STATUS **PRODUCTION**

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE WITHOUT WRITTEN PERMISSION FROM THE HILLIARD CORP. © COPYRIGHT THE HILLIARD CORPORATION, ALL RIGHTS RESERVED. MAKE FROM	UNLESS OTHERWISE SPECIFIED <input checked="" type="checkbox"/> MACHINE <input type="checkbox"/> MICRONS	<b>Hilliard</b> THE HILLIARD CORPORATION 100 WEST FOURTH STREET ELMIRA, NEW YORK 14902 DIMENSIONS ARE IN INCHES ( ) DIMENSIONS IN MM	DRAWN BY: GF DATE: 06/28/00	TITLE HS611-200-SERIES SEPARATOR CARTRIDGE
	UNLESS OTHERWISE SPECIFIED BREAK CORNERS .015 MAX		CHECKED BY: GLF DATE: 06/28/00	
	UNLESS OTHERWISE SPECIFIED: FRACTIONAL DIMENSIONS - ± 1/16 DECIMAL DIMENSIONS - .001 - ± .015 ANGLES - ± 2'		APPROVED BY: GLF DATE: 06/28/00	
	SIMILAR TO:		SCALE: FULL	
			SHEET 1 OF 1	DD-700-104 <b>C</b>