

				Actuators	
 Fixed Actuator suitable for mounting on either sliding or hinged doors. Padlock through tongue. 2500N Retention force. 	Features	Description	Part No.		
	Features & Benefits	Fixed Actuator	TAF		TAF
 Handle actuators suitable for brackettess mounting to hinged doors. 4mm misalignment feature. TAH actuator can be converted to a TAS actuator on site (special tool required). Padlock through tongue. 2500N Retention force. Quick bolt to Aluminium extrude (no brackets). 	Features	Description	Part No.		-
suitable for atting to hinged serit feature. The be converted to a site (special tool tongue) Torigue.	Features & Benefits	Handle Actuator - Hinged Door	ТАН		TΔΗ
 Handle actuators suitable for brackettess mounting to sliding doors. 4mm misalignment feature. TAS actuator can be converted to a TAH actuator on site (special too required). Padlock through tongue. 2500N Retention force. Quick bolt to Aluminium extrude (rescribed). 	Features	Description	Part No.		-
Handle actuators suitable for brackettess mounting to sliding doors. 4mm misalignment feature. TAS actuator can be converted to a TAH actuator on site (special tool required). Padlock through tongue. 2500N Retention force. Quick bolt to Aluminium extrude (no brackets).	Features & Benefits	Handle Actuator - Sliding Door	TAS	To All States	TAS
Blank Handle (without use on inside of doors.	Features & Benefits	Description	Part No.		4
 Blank Handle (without actuator) for use on inside of doors. 		Blank Handle	THB		THB
Intuitive handle actuator giving latching feature on hinged doors 4mm misalignment feature. Lock out feature. Handing can be changed on site. Prevents force of door slamming against interlock. 2500N Retention force.	Features & Benefits	Description	Part No.		TEN
Intuitive handle actuator giving latching feature on hinged doors. Amm misalignment feature. Lock out feature. Landing can be changed on site. Landing can be changed on site.		Handle Actuator - (no internal knob)	TEN		
 Intuitive handle actuator giving latching feature on hinged doors. 4mm misalignment feature. Lock out feature. Handing can be changed on site. Prevents force of door slamming against interlock. 2500N Retention force. Quick bolt to Aluminium extrude. Internal knob allows actuator to be retracted but not extended. 	Features	Description	Part No.		-1
	Features & Benefits	Handle Actuator	TEH		TEH

All Actuators to be used in combination with a THM head



Note: The internal knob on TEH handle does not override the plenoid or lock. A TRX/Z nternal release element)